

Product: Scale Specifications

<b>Weighing Capacity</b>	2 kg (S2) / 5 kg (S5)
<b>Display resolution</b>	1 g (on franking system display)
<b>Platform area</b>	152 x 152 mm
<b>Operating temperature range</b>	10°C - 40°C
<b>Storage temperature range</b>	-15°C - 55°C
<b>Air humidity range</b>	10% - 90% relative humidity
<b>Power supply</b>	Powered from franking system via connecting cable
<b>Dimensions</b>	153 mm wide, 187 mm deep, 42 mm high
<b>Net Weight</b>	652g

Product: Mailmax franking machines

<b>Capacity</b>	Up to 4,000 franks per hour	
<b>Max. Letter thickness</b>	6 - 8mm depending on contents	
<b>Screen</b>	Frama ComTouch™ (9.5x7.3 cm)	
<b>Printing Technology</b>	Ink Jet	
<b>Ink cassette</b>	Up to 30,000 franks (dependant on postal requirements and the number of clichés used)	
<b>Electronics</b>	Microprocessor controlled	
<b>Electrical data</b>		
<b>Voltage</b>	230 V/50Hz	110 V/60Hz
<b>Nominal Current</b>	0.6A	1.2A
<b>Consumption</b>	140W	140W
<b>Fusing</b>	T1.25AH	T2.0AH
<b>Dimensions</b>		
<b>Depth</b>	381mm	
<b>Width</b>	286mm	
<b>Height</b>	191mm	
<b>Weight</b>	8.7Kg	

Product: OfficeMail franking machines

<b>Capacity</b>	Up to 3,000 franks per hour	
<b>Max. Letter thickness</b>	6mm	
<b>Screen</b>	Frama ComTouch™ (9.5x7.3 cm)	
<b>Printing Technology</b>	Thermotransfer	
<b>Ink cassette</b>	1,200 – 3,600 franks (dependant on postal requirements and the number of clichés used)	
<b>Electronics</b>	Microprocessor controlled	
<b>Electrical data</b>		
<b>Voltage</b>	230 V/50Hz	110 V/60Hz
<b>Nominal Current</b>	0.6A	1.2A
<b>Consumption</b>	140W	140W
<b>Fusing</b>	1.25A (slow blow)	2.0A (slow blow)
<b>Dimensions</b>		
<b>Depth</b>	330mm	
<b>Width</b>	257mm	
<b>Height</b>	175mm	
<b>Weight</b>	6Kg	

Product: Ecomail Franking Machines

<b>Capacity</b>	Up to 2,000 franks per hour	
<b>Max. Letter thickness</b>	6mm	
<b>Screen</b>	Frama ComTouch™ (9.5x7.3 cm)	
<b>Printing Technology</b>	Thermotransfer	
<b>Ink cassette</b>	1,200 – 3,600 franks (dependant on postal requirements and the number of clichés used)	
<b>Electronics</b>	Microprocessor controlled	
<b>Electrical data</b>		
<b>Voltage</b>	230 V/50Hz	110 V/60Hz
<b>Nominal Current</b>	0.6A	1.2A
<b>Consumption</b>	140W	140W
<b>Fusing</b>	1.25A (slow blow)	2.0A (slow blow)
<b>Dimensions</b>		
<b>Depth</b>	330mm	
<b>Width</b>	257mm	
<b>Height</b>	175mm	
<b>Weight</b>	6Kg	

Product: P700 Folding Machines

<b>Paper (recommendation for optimal use)</b>	60 – 150 g/m <sup>2</sup> .	
<b>Paper Width</b>	75 – 311mm	
<b>Paper Length</b>	105 – 420 mm	
<b>Loading Capacity</b>	150 sheets max (depending on weight/type)	
<b>Ideal Stack Height</b>	12 – 14 mm	
<b>Folding Speed</b>	5,200 sheets per hour (depending on weight/type)	
<b>Folding Volume (recommendation)</b>	Average volume of 20,000 folds per month	
<b>Electrical data</b>		
<b>Voltage</b>	230 V/50Hz	110 V/60Hz
<b>Power Supply</b>	24V-DC2.5-60W	
<b>Dimensions (in storage mode)</b>		
<b>Depth</b>	270mm	
<b>Width</b>	440mm	
<b>Height</b>	250mm	
<b>Dimensions (in working mode)</b>		
<b>Depth</b>	390mm	
<b>Width</b>	440mm	
<b>Height</b>	450mm	
<b>Weight</b>	10.5kg	

Product: Letter Opener B300

<b>Cutting rate (per minute)</b>	60 – 150 g/m <sup>2</sup> .
<b>Letter Passage</b>	
<b>Thickness</b>	Max. 6.5 mm
<b>Stack Height</b>	Max 50 mm
<b>Dimensions (excluding letter collector)</b>	331L x 200D x 142H
<b>Dimension of the letter collector</b>	290L x 190D x 132H
<b>Net Weight (excluding letter collector)</b>	3.5kg
<b>Net Weight (including letter collector)</b>	4.1kg
<b>Mains Supply</b>	
<b>Voltage</b>	110-240 V, 5-60 Hz
<b>Fuse</b>	T 2.0 amp

Product: Letter Feeder LF8550

<b>Capacity Per Hour</b>	Up to 6,500 in C4 format (324x229 mm) Up to 9,400 in C6 format (162x114 mm)	
<b>Letter Formats</b>		
<b>With foldable feeder extension</b>	Up to B4 vertically addressed (max height 362mm)	
<b>Without foldable feeder extension</b>	Up to C4/C5 vertically addressed (max height 229mm)	
<b>Minimum length</b>	143 mm	
<b>Minimum height</b>	96 mm	
<b>Letter thickness</b>	8 mm (dependent on letter contents)	
<b>Maximum envelope flap height</b>	60 mm	
<b>Minimum envelope flap angle</b>	15°	
<b>Glue type</b>	synthetic resin-based mixed glue	
<b>Water container capacity</b>	530 ml (sufficient for approx. 10,000 C6/5 envelopes)	
<b>Sealing without franking</b>	yes, with item counter	
<b>System Dimensions</b>		
<b>Length*</b>	1,360 mm	
<b>Depth with feeder extension</b>	505 mm	
<b>Depth without feeder extension</b>	390 mm	
<b>Height</b>	245 mm	
<b>Weight**</b>	27.8kg	
<b>Noise Level</b>	Complete system 61 db(A)	
<b>Voltage***</b>	230 V / 50 Hz	OR 110 V / 60 Hz
<b>Nominal Current</b>	0.25 A	OR 0.50 A
<b>Power</b>	60W	
<b>Fuse</b>	630 mA FST	1.25 A FST

\* Envelope support roller folded out/letter collector at maximum extension

\*\* Incl. franking system and additional table (option 50) and feeder/sealer module (option S)

\*\*\* Automatic, i.e. system is self-adjusting

Product: Letter Feeder LF4500

<b>Capacity Per Hour</b>	Approx. 3900 in C4 format (324x229 mm) Approx. 5200 in C6 format (162x114 mm)
<b>Letter Formats</b>	
<b>Maximum format</b>	C4 horizontally addressed
<b>Minimum length</b>	143 mm
<b>Minimum height</b>	96 mm
<b>Letter thickness</b>	8 mm (dependent on letter contents)
<b>Sealing Capacity (optional)</b>	
<b>Maximum envelope flap height</b>	60 mm
<b>Minimum envelope flap angle</b>	≥15°
<b>Glue type</b>	synthetic resin-based mixed glue
<b>Water container capacity</b>	530 ml (sufficient for approx. 10,000 C6/5 envelopes)
<b>Sealing without franking</b>	yes, with item counter
<b>System Dimensions</b>	
<b>Length*</b>	985 mm
<b>Depth</b>	381 mm
<b>Height</b>	225 mm
<b>Weight**</b>	18.6 kg
<b>Noise Level</b>	Complete system 61 db(A)

\* Envelope support fully extended / incl. franking system, excl. letter collector

\*\* Incl. franking system sealing unit (option S) and letter collector